

SF₆ Verify

proving your SF₆ analysis

from the world leaders in SF₆ analysis and handling



EMT's new Verify range of precision SF6 gas verification products set the industry benchmark in quality and stability for proving your SF6 analysis.

EMT Quality

- EMT Verify offers the most complete SF6 verification gas mixture for peace of mind ensuring results confidence when using your SF6 gas analyser.
- EMT Verify gas standards can be used with all types of SF6 analyser.
- EMT Verify meets NIST* quality standards and all gases come complete with NIST* traceable certificates of analysis.

EMT Value

- The EMT Verify starter kit provides users with a complete and easy to use start up kit for proving your SF6 analysis.
- EMT Verify provides exceptional verification gas products and services at competitive prices.
- EMT Verify gives customers the highest level of technical-added-value with quality, reliability and technical excellence at the heart of its service.

*NIST = National Institute of Standards and Technology

emt
Energy Maintenance Technologies Ltd
Unit A6a Barton Industrial Estate
Barton le Clay
Bedfordshire MK45 4RP
Tel: +44 7535 900214
Tel: +44 7979 527292
www.emt.uk.com

CERTIFICATE OF ANALYSIS

Date: July 31, 2015
Order Number:
Lot Number:

Customer: Energy Maintenance Technologies Ltd
Use Before: 10/31/2016

Component	Specification (+/- 10%)	Analytical Result (+/- 2%)
Sulfur Dioxide	75 PPM	77 PPM
Nitrogen	Balance	Balance

Cylinder Size: 2.0 Cu. Ft.
Contents: 58 Liter

Valve: 5/8" -18UNF
Pressure: 500 psig

NIST Weight Certificate Number(s): 240756-1

The calibration gas prepared by EMT is considered a certified standard. It is prepared by gravimetric or partial pressure techniques. The calibration standard provided is certified against EMT's G.M.I.S. (Gas Manufacturer's Intermediate Standard) which is either prepared by weights traceable to the National Institute of Standards and Technology (NIST) or by using NIST Standard Reference Materials where available.

TECHNICAL RECOMMENDATIONS
For best results, use the following procedure when using Reactive Gas Mixtures and always use the shortest length possible of Teflon Tubing between the Cylinder Regulator Hose Barb and the Gas Detection Instrument. Turn the regulator on before connection is made with the cylinder, allowing any trapped air to be purged from the regulator. Be sure to turn the regulator off as soon as the regulator is fully connected. Always ensure delivery tubing is compatible with the Gas. Do not store this cylinder off as the regulator installed due to possible leakage or long-term reaction with internal components of the regulator. Follow instrument manufacturer's instruction manual.

Analyst:

Certificate of analysis



Specialisation

EMT's vast experience and technical knowledge enables us to offer the most difficult reactive gas mixtures with confidence and our guarantee of quality and stability.

EMT SF6 Verification Gas Check

EMT Starter Kit (VGAS-SK-3)

The EMT Starter Kit comprises of:

- 1 x 99.99% SF6
- 1 x 200 ppm H2O
- 1 x 75 ppm SO2
- 1 x Dial-A-Flow Regulator
- 1 x Carry case

Verification Refill Gases

- SF6 (part number VGAS-SF6-99-2)
- H2O (part number VGAS-SO2-75-2)
- SO2 (part number VGAS-H2O-200-2)



Part Number	Verification Gas Starter Kit	Accuracy
VGAS-SK-3	Verify gas starter kit including: 3 x 58 ltr gas bottles (SF6/SO2/ H2O) + soft carry case and regulator /Swagelok 1/2" adapter.	
	SF6, 58 litre non refillable gas cylinder, 99.99%.	+/- 1%*
	SO2, 58 litre non refillable gas cylinder, 75 ppm.	+/- 3 ppm*
	H2O, 58 litre non refillable gas cylinder, 200 ppm.	+/- 40 ppm*

Part Number	Verification Refill Gases	Accuracy
VGAS-SF6-99-2	Qty 2, SF6, 58 litre non refillable gas cylinder, 99.99%.	+/- 1%*
VGAS-SO2-75-2	Qty 2, SO2, 58 litre non refillable gas cylinder, 75 ppm.	+/- 3 ppm*
VGAS-H2O-200-2	Qty 2, H2O, 58 litre non refillable gas cylinder, 200 ppm.	+/- 40 ppm*

*Note: Accuracy is combined tolerance calculated from certificate of analysis of gas container plus the EMT SF6 zerowaste Analyser accuracy.

Part Number	Accessories
VGAS-Reg-Adt	Additional Verify gas regulator fitted with Swagelok male 1/2" quick connect adapter
VGAS-Hose	2 metre hose for use with EMT Zerowaste Analyser
VGAS-VCC	Verify soft carry case for 3 gas bottles

Regulator

Part Number	Dial-A-Flow
Valve Inlet	C10
Fits Cylinder	58L
Flow Rate	0.3 - 8 LPM (0.07-0.8 gpm) Selectable
Gauge PSIG	1500 PSIG (103 Bar)
Material	Aluminium



Carry Case

The EMT Verify Carrying Case is ideal for safely storing and transporting all EMT Verify Gas Cylinders and Regulators.



EMT Verify works with:



IR zerowaste®
SF6 Analyser

asserolyz-IR™
SF6 Analyser

Zerowaste® CMS



EMT Verify products are compatible
with all leading SF6 Analyser brands

Cylinder

Part Number	58L
Pressure	500 PSIG (34.5 Bar)
Gas Type	All reactive mixtures (upon request)
Dimensions	14.25" x 4.25" (36.2 x 10.8 cm)
Volume Capacity Empty	2.2 Litres (0.077 Cu Ft)
Material	Aluminium alloy
Weight	2lbs 5oz (1.051 Kg)
Valve Outlet	5/8" - 18 UNF (C10)
Regulator	VGAS-REG-ADT series
Volume Capacity with gas	58 Litres (2.05 Cu Ft) at 70°F (21.1°C) and 500 PSIG (34.4 Bar)

We use the highest quality cylinder in the industry, which meet and exceed all criteria of its customers and appropriate regulatory authorities.

PRECISION GAS MIXTURE	
COMPONENTS	CONCENTRATION (MOLE%)
SULPHUR DIOXIDE (SO2)	75 PPM
NITROGEN (N2)	BALANCE
MFG Date: XXX-XX UN1956	Use Before: xx/xx/xxxx L271067
Contents: 2.05 Cu.Ft. 58L @ 70 Deg. F and 500 PSIG DOT-39 NRC 500/625 M1039	
GHS 010	
This product meets or exceeds the requirements of the Gas Detection Equipment Manufacturer.	

Example cylinder bottle label

Energy Maintenance Technologies Ltd
Unit A6 Barton Industrial Estate
Barton le Clay
Bedfordshire
MK45 4RP
United Kingdom
Tel: + 44 (0) 7535 900214 | Tel: +44 (0) 7979 527292
Email: enquiries@emt.uk.com
www.emt.uk.com

For details of EMT local distributors around the world email: enquiries@emt.uk.com

MKT-012

